

309 U.S. CBP Importer Security Filing (ISF-10 and ISF-5)

Functional Group ID=**SF**

Introduction:

This X12 Transaction Set contains the format and establishes the data contents of the U.S. Customs and Border Protection (USCBP) Stand Alone Security Filing using the (309) transaction set. This document is intended for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used by carriers, NVOCC's, brokers and/or Third Party contactors submitting on behalf of importers regarding cargo arriving in or departing from oceangoing vessels. Please Note the 'SF' Functional Group identifier should be used exclusively for Stand Alone ISF Filings.

This Implementation Guideline uses the ASC X12 6050 Standards Version/Release as its base. The transaction structure has been altered to accommodate Aduana Mexico SAT implementation requirements.

Notes:

This transaction set is final and conforms to the published Importer Security Filing and Additional Carrier Requirements interim final rule. It will continue to be posted on this page for the ease of the Trade.

Importer Security Filing (ISF-10):

1. Manufacturer Name and Address
2. Seller Name and Address
3. Buyer Name and Address
4. Ship to Name and Address
5. Scheduled Container Stuffing Location
6. Consolidator Name and Address
7. Importer of Record
8. Consignee identification number
9. Country of origin where goods were manufactured, produced or grown
10. Harmonized Tariff Schedule at minimum 6-digit level

Importer Security Filing Information for FROB, T&E, and IE (ISF-5):

1. Booking Party Name and Address
2. Foreign Port of Unlading
3. Place of Delivery
4. Ship to Name and Address
5. Harmonized Tariff Schedule at minimum 6-digit level

The above Importer 5 data elements can be consolidated with the standard 309 Bill of Lading transaction set by including the above data elements at the locations identified in the appropriate USCBP implementation guide.

Special Messaging constraints:

Limit one Interchange (ISA-IEA) per message transmission.

Limit one message Group (GS-GE) per message transmission.

Multiple transaction sets (ST-SE) of the same Transaction Set Identifier Code (i.e., 309) are allowed per message transmission.

All elements included in this Guideline are considered usable unless identified otherwise in the element level gray notes.

Element delimiters used in this transaction should be ' * ' (asterisk). No blanks between delimiters if element is null. Segment delimiters used in this transaction should be one byte with a value of hex '15'.

A segment delimiter should be the last byte of data in the message transmission data stream.

Transmit ONLY uppercase ENGLISH alphabetic data.

USCBP usage: D = Dependent (Conditional)

	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat
M	010	ISA	Interchange Control Header	M	1	
M	020	GS	Functional Group Header	M	1	
M	030	ST	Transaction Set Header	M	1	
M	040	M10	Manifest Identifying Information	M	1	
	043	N9	Reference Identification	O	5	
			LOOP ID - NM1			2
	049	NM1	Individual or Organizational Name	O	1	
	050	DMG	Demographic Information	O	1	
	050	REF	Reference Identification	O	10	
			LOOP ID - P4			20
M	050	P4	U.S. Port Information	M	1	
			LOOP ID - LX			9999
M	060	LX	Assigned Number	M	1	
	090	N9	Reference Identification	O	999	
			LOOP ID - N1			99
	100	N1	Name	O	1	
	110	N3	Address Information	O	2	
	120	N4	Geographic Location	O	1	
	125	DMG	Demographic Information	O	1	
			LOOP ID - M12			1
	150	M12	In-bond Identifying Information	O	1	
	160	R4	Port or Terminal	O	2	
			LOOP ID - VID			999
	170	VID	Conveyance Identification	O	1	
			LOOP ID - N1			999
	184	N1	Name	O	1	
	190	N3	Address Information	O	1	
	190	N4	Geographic Location	O	1	
			LOOP ID - N10			999
Must Use	190	N10	Quantity and Description	O	1	
M	200	SE	Transaction Set Trailer	M	1	
M	220	GE	Functional Group Trailer	M	1	
M	240	IEA	Interchange Control Trailer	M	1	

Segment: **ISA** Interchange Control Header
Position: 010
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ISA01	I01	Authorization Information Qualifier	M ID 2/2
			Code to identify the type of information in the Authorization Information	
			Always '00'	
			00	No Authorization Information Present (No Meaningful Information in I02)
M	ISA02	I02	Authorization Information	M AN 10/10
			Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	
			Always 10 spaces.	
M	ISA03	I03	Security Information Qualifier	M ID 2/2
			Code to identify the type of information in the Security Information	
			Always '00'	
			00	No Security Information Present (No Meaningful Information in I04)
M	ISA04	I04	Security Information	M AN 10/10
			This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	
			Always 10 spaces.	
M	ISA05	I05	Interchange ID Qualifier	M ID 2/2
			Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified	
			Always 'ZZ'	
			ZZ	Mutually Defined
M	ISA06	I06	Interchange Sender ID	M AN 15/15
			Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element	
			Sender identifier. Up to 4 alpha/numeric characters. Value must contain the CAAT Code or the identity of the Service Center if applicable. May be identical to the GS02.	
M	ISA07	I05	Interchange ID Qualifier	M ID 2/2
			Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified	
			Always 'ZZ'	
			ZZ	Mutually Defined

M	ISA08	I07	Interchange Receiver ID Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them Values: 'CUSTOMSTST' - Testing 'CUSTOMS' - Production	M	AN 15/15
M	ISA09	I08	Interchange Date Date of the interchange Date as YYMMDD where: YY - Year MM - Month of Year DD - Day of Month	M	DT 6/6
M	ISA10	I09	Interchange Time Time of the interchange Time as HHMM where: HH - Hour MM - Minute	M	TM 4/4
	ISA11	I65	Repetition Separator Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator Repetition Separator = "^" (caret)	O	AN 1/1
	ISA12	I11	Interchange Control Version Number This version number covers the interchange control segments Always '00605' 00605 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2006	O	ID 5/5
M	ISA13	I12	Interchange Control Number A control number assigned by the interchange sender	M	N0 9/9
M	ISA14	I13	Acknowledgment Requested Code sent by the sender to request an interchange acknowledgment (TA1) Always '0' 0 No Acknowledgment Requested	M	ID 1/1
M	ISA15	I14	Usage Indicator Code to indicate whether data enclosed by this interchange envelope is test, production or information Always 'P' P Production Data	M	ID 1/1
M	ISA16	I15	Component Element Separator Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator Always ':' (colon)	M	AN 1/1

Segment:	GS	Functional Group Header
Position:	020	
Loop:		
Level:		
Usage:	Mandatory	
Max Use:	1	
Purpose:	To indicate the beginning of a functional group and to provide control information	
Syntax Notes:		
Semantic Notes:	1 GS04 is the group date. 2 GS05 is the group time. 3 The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.	
Comments:	1 A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.	

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	GS01	479	Functional Identifier Code	M ID 2/2
Code identifying a group of application related transaction sets				
Always 'SF'				
SF Stand Alone Security Filing [ISF-10 or ISF-5]				
M	GS02	142	Application Sender's Code	M AN 2/15
Code identifying party sending transmission; codes agreed to by trading partners				
Sender identifier. Up to 4 alpha/numeric characters. Value must contain the CAAT Code or the identity of the Service Center if applicable. May be identical to the ISA06.				
M	GS03	124	Application Receiver's Code	M AN 2/15
Code identifying party receiving transmission; codes agreed to by trading partners				
Values:				
'CUSTOMSTST' - Testing				
'CUSTOMS' - Production				
M	GS04	373	Date	M DT 8/8
Date expressed as CCYYMMDD				
Date as CCYYMMDD where:				
CC - Century				
YY - Year				
MM - Month of Year				
DD - Day of Month				
M	GS05	337	Time	M TM 4/8
Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
Time as HHMM where:				
HH - Hour				
MM - Minute				
M	GS06	28	Group Control Number	M N0 1/9
Assigned number originated and maintained by the sender				

M	GS07	455	Responsible Agency Code	M ID 1/2
			Code used in conjunction with Data Element 480 to identify the issuer of the standard	
			Always 'X'	
			X	Accredited Standards Committee X12
M	GS08	480	Version / Release / Industry Identifier Code	M AN 1/12
			Code indicating the version, release, sub release, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and sub release, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed	
			Always '006050'	
			006050	Standards Approved for Publication by ASC X12 Procedures Review Board through October 2006

Segment: **ST** Transaction Set Header
Position: 030
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			Use '309' to represent ISF Security Filing where the GS02 = 'SF'	
			309 U.S. Customs Manifest	
M	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	

Segment:	M10	Manifest Identifying Information
Position:	040	
Loop:		
Level:		
Usage:	Mandatory	
Max Use:	1	
Purpose:	To transmit manifest identifying information	
Syntax Notes:	1	If either M1005 or M1011 is present, then the other is required.
	2	At least one of M1006 or M1005 is required.
	3	M1004 is Lloyd's vessel code.
	2	M1007 is used for the six-digit Numeric Manifest Sequence Number.
Semantic Notes:	3	M1011 indicates if the transmission involves an in-bond participant. A "Y" indicates it does; an "N" indicates it does not.
	4	M1012 is a unique identification number for the manifest assigned by the originator of the manifest with a maximum length of 15.
Comments:	1	M1003 is the code identifying the country in which the ship (vessel) is registered.
	2	M1008 is used for number of bills lading. (Maximum five-digits.)

Data Element Summary					
	Ref. Des.	Data Element	Name	Attributes	
M	M1001	140	Standard Carrier Alpha Code	M	ID 2/4
			Standard Carrier Alpha Code		
			Mexican CAAT code. Entity initiating Importer Security Filing.		
M	M1002	91	Transportation Method/Type Code	M	ID 1/2
			Code specifying the method or type of transportation for the shipment		
			Code specifying the method or type of transportation for the shipment.		
			O - ocean		
Not Used	M1003	26	Country Code	O	ID 2/3
Not Used	M1004	597	Vessel Code	X	ID 1/8
Not Used	M1005	182	Vessel Name	O	AN 2/28
Not Used	M1006	55	Flight/Voyage Number	O	AN 2/30
Not Used	M1007	127	Reference Identification	O	ID 2/3
Not Used	M1008	380	Quantity	O	R 1/15
M	M1009	256	Manifest Type Code	O	ID 1/1
			Code identifying the type of manifest transmitted		
			Required. ISF Submission Type Code.		

When an ISF-10 submission type is used, the SF data set must have a segment for each of the following Entity Codes: MF, SE, BY, ST, CS, CN, and LG.

When an ISF-5 submission type is used, the ISF data set must have a segment for each of the following Entity codes: BKP and ST.

In cases where ISF Submission Types '3' or '4' have been used and another replace transaction must be submitted to CBP, please continue to use these ISF Submission Types. Do NOT use '1' or '2' after you have modified an ISF using '3' or '4'.

- 1 Importer Security Filing 10 [ISF-10]
- 2 Importer Security Filing 5 [ISF-5]

3 ISF-5 submission type is being changed to an ISF-10
4 ISF-10 submission type is being changed to an ISF-5

Not Used	M1010	897	Vessel Code Qualifier	X	ID 1/1
Not Used	M1011	1073	Yes/No Condition or Response Code	O	ID 1/1
Not Used	M1012	127	Reference Identification	O	AN 1/80
Not Used	M1013	353	Transaction Set Purpose Code	O	ID 2/2
M	M1014	346	Application Type Code	O	ID 2/2

Code identifying an application

Required. Importer Security File Shipment Type Code.
This element must be '01' for ISF-5.

Shipment Type 11 is used for low-value shipments where formal entry is not required. When this shipment type is used, the SF data set must have an N9 segment with a valid shipment sub-type, an estimated value (U.S. dollars), estimated quantity (smallest external packaging units) and estimated weight (kg or lbs) of the shipment. A bond will not be required to cover the ISF requirements for eligible shipments.

01	Standard or Regular filings
02	To Order Shipments
03	Household Goods/Personal Effects
04	Military, Government
05	Diplomatic Shipment
06	Carnet
07	US Return Goods
08	FTZ Shipments
09	International Mail Shipments
10	Outer Continental Shelf Shipments
11	Informal

M1015	580	Amendment Type Code	O	ID 1/1
-------	-----	---------------------	---	--------

Code identifying type of manifest amendment

Required. Values accepted by USCBP.

A	Add Importer Security Filing
D	Delete Importer Security Filing
R	Replace Importer Security Filing

M1016	393	Amendment Code	O	ID 2/2
-------	-----	----------------	---	--------

Code giving the reasons for the amendment of the manifest record

Importer Security Filing (ISF) Action Reason Code. Required if M1015 = 'A' or 'R'

Valid Action Reason Codes:

CT = Complete Transaction – All data is present, no special flexibility rules apply. If "CT" is used, the ISF can be updated if necessary, but SAT does not require the ISF to be updated.

FR = Flexible Range – A range of data for the Manufacturer, Ship To party, Country of Origin, or Commodity HTSUS number has been provided. The ISF must be updated as soon as better information becomes available, but never later than 24 hours prior to arrival. If "FR" is used, SAT expects to receive a timely update.

FT = Flexible Timing – The CS (Consolidator) and or LG (Stuffing location) has not been provided. The ISF must be updated as soon as better information becomes available, but never later than 24 hours prior to arrival. If "FT" is used, CBP expects to receive a timely update.

Not Used M1017 256

FX = Flexible Range and Flexible Timing - A range of data as described in “FR” has been provided and the CS (Consolidator) and or LG (Stuffing location) has not been provided. The ISF must be updated at a later date as soon as better information becomes available, but in no case later than 24 hours prior to arrival. If “FX” is used, SAT expects to receive a timely update.

Manifest Type Code **O** **ID 1/1**

Segment:	N9 Reference Identification
Position:	043
Loop:	
Level:	
Usage:	Optional
Max Use:	5
Purpose:	To transmit identifying information as specified by the Reference Identification Qualifier
Syntax Notes:	1 At least one of N902 or N903 is required. 2 If N906 is present, then N905 is required. 3 If either C04003 or C04004 is present, then the other is required. 4 If either C04005 or C04006 is present, then the other is required.
Semantic Notes:	1 N906 reflects the time zone which the time reflects. 2 N907 contains data relating to the value cited in N902.
Comments:	
Notes:	At least one interaction of N901 and N902 is required to communicate 'FC' - Filer/Agent Code.

Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element		
M	N901	128	M ID 2/3
		Reference Identification Qualifier	
		Code qualifying the Reference Identification	
		Values accepted by SAT	
		7U	Related Transaction Reference Number
			Required if M1015 = 'R' or 'D'. SAT will assign a unique ISF Transaction Number (FFFFNNNNNNNNNNNN) that will be returned in the output response from CBP to the ISF filer in the 355. FFFF=Filer code and NNNNNNNNNNNN=numeric sequence number.
		FC	Filer Code Issued by Customs
			Required.
			This value is also referred to as Filer/Agent Code.
			Note: When the participant is transmitting on behalf of itself this value is the same value as appears in the GS02. Otherwise the Filer/Agent Code must be entered as a CAAT indicating on whose behalf the ISF is being transmitted.
		SCI	Surety Code Identifier
			Required if Bond Activity Code is '16' and the Bond Type is '9'.
		SBN	Bond Reference Number
			This is NOT the same as the bond number.
			Required if Bond Activity Code is '16' and the Bond Type is '9'.
		6C	Carnet issuing Country Code and Carnet Number
			6C is required if Shipment Type Code (M1014) = '06'
		CR	User-defined Reference Number.
			Optional user-defined field that will be returned in both the 355 and 350 messages.
		FN	Full Name of ISF Filer.
		SBT	Shipment Sub-Type
			If the Shipment Type Code (M1014) is '11', then an N9 segment is required with 'SBT' in the N901, a Shipment Sub-Type in the N902, and the estimated value, estimated quantity, and estimated weight in the N907.

Valid Shipment Sub-types:
 01 = Section 321 Shipments; see 19 USC § 1321
 02 = Informal Shipments; see 19 CFR § 143.21
 03 = General Note 3(e) Shipments; see General Note 3(e)
 to the Harmonized Tariff Schedule of the United States
 (HTSUS)

For SAT

HO The HO qualifier in N901 is used by
 The carriers to report the master bill
 Of lading number associated with the
 House bill.

MXC The MXC qualifier is used by carriers
 To report the Mexican CAAT number

MXE The MXE qualifier is used by carriers
 To report the Mexican export bonded
 Warehouse number. This is for
 Mexican export transactions and
 Usage. Refer to schedule located
 In <http://www.gob.mx/refx12>
 appendix

MXI The MXI qualifier is used by carriers
 To report the Mexican import bonded
 Warehouse number. This is for
 Mexican export transactions and
 Usage. Refer to schedule located
 In <http://www.gob.mx/refx12>
 appendix
 CAMIR appendix O contains valid
 Mexican warehouse numbers

N902 127 Reference Identification X AN 1/30

Reference information as defined for a particular Transaction Set or as
 specified by the Reference Identification Qualifier

A value representing Transaction Number, Surety Code, Bond Reference
 Number, Carnet information, or Filer/Agent Code.

Note: SCI (surety code) and SBN (bond reference number) are required if
 Bond Activity Code is '16' and the Bond Type is '9'.

When the Reference Identifier Qualifier = 6C, the Carnet issuing Country Code
 and Carnet Number must be provided in a concatenated format as follows:
 2-digit Country Code (Carnet issuing Country) followed by Carnet Number.

To identify one or more reference numbers or identification numbers as
 specified by the Reference Qualifier

Not Used **N903 369 Free-form Description X AN 1/45**

Not Used **N904 373 Date O DT 8/8**

Not Used **N905 337 Time X TM 4/8**

Not Used **N906 623 Time Code O ID 2/2**

N907 C040 Reference Identifier X

To identify one or more reference numbers or identification
 numbers as specified by the reference Qualifier

C04001 128 Reference Identification Qualifier M ID 2/3

Code qualifying the Reference Identification

EMV Estimated Monetary Value

C04002 127 Reference Identification M AN 1/30

Estimated Monetary Value in whole U.S. Dollars. The value must be greater
 than zero.

C04003	128	Reference Identification Qualifier	X	ID 2/3
		Code qualifying the Reference Identification		
		A code representing the unit of measure for the estimated quantity. Refer to the CAMIR Importer Security Filing SF13 record for valid codes. The standard generic unit of pieces (PCS) is acceptable when there are multiple units of measure associated with the shipment.		
C04004	127	Reference Identification	X	AN 1/30
		Estimated Quantity in the smallest external packaging unit. Input only whole numbers; no decimals or fractions. The value must be greater than zero..		
C04005	128	Reference Identification Qualifier	X	ID 2/3
		Code qualifying the Reference Identification		
		EWK Estimated Weight in Kilos		
		EWL Estimated Weight in Pounds		
C04006	127	Reference Identification	X	AN 1/30
		Total weight in pounds or kilos. Input only whole numbers; no decimals or fractions. The value must be greater than zero.		

Segment:	NM1 Individual or Organizational Name
Position:	049
Loop:	NM1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To supply the full name of an individual or organizational entity
Syntax Notes:	1 If either NM108 or NM109 is present, then the other is required. 2 If NM111 is present, then NM110 is required.
Semantic Notes:	1 NM102 qualifies NM103.
Comments:	1 NM110 and NM111 further define the type of entity in NM101.
Notes:	One NM1 segment is required to report the ISF Importer for all transactions. A second NM1 segment is required to report the Importer of record when M1009 is an ISF-10 submission type code. If NM108 = 34 and M1014 = 01, 02, 04, 07, 08, 09, or 10, then the SSN must be on file with CBP. If NM108 = 34, and M1014 = 03, 05, 06 or 11, and the SSN is NOT on file with CBP, then data must be provided in the NM103, NM104, NM105, and NM107 (if necessary) and in the DMG segment. If NM108 = PN, then data must be provided in the NM103, NM104, NM105, and NM107 (if necessary) and in the DMG segment.

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
M	NM101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		Values accepted by SAT. One NM1 loop must be present for each value when M1009 = '1'.	
		IOR Importer of Record	
		ISF ISF Importer	
M	NM102	1065 Entity Type Qualifier	M ID 1/1
		Code qualifying the type of entity	
		Values accepted by SAT.	
		1 Person	
		2 Non-Person Entity	
	NM103	1035 Name Last or Organization Name	O AN 1/35
		Individual last name or organizational name	
		Last Name of the ISF Importer or Importer of Record.	
	NM104	1036 Name First	O AN 1/25
		Individual first name	
		First Name of the ISF Importer or Importer of Record.	
	NM105	1037 Name Middle	O AN 1/25
		Individual middle name or initial	
		Middle Name of the ISF Importer or Importer of Record.	
X	NM106	1038 Name Prefix	O AN 1/10
		Prefix to individual name	
	NM107	1039 Name Suffix	O AN 1/10
		Suffix to individual name	
		Name Suffix of the ISF Importer or Importer of Record.	
	NM108	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code in NM109	

		Required. Values accepted by USCBP.			
		2	Standard Carrier Alpha Code (SCAC)		
			Qualifier may only be used for ISF Importer when filing an ISF Submission Type Code is an ISF-5 (M1009)		
		24	Employer's Identification Number		
		34	Social Security Number		
		CU	U.S. Customs and Border Protection [USCBP] Assigned Importer Number		
		PN	Passport Number		
			Passport may only be used for Shipment Type Codes 03, 05, or 06,		
NM109	67	Identification Code		X	AN 2/80
Code identifying a party or other code					
Required.					
ID number used to further identify the code in NM108.					
Valid formats are:					
		NN-NNNNNNXX	Internal Revenue Service (IRS) Number		
		NNN-NN-NNNN	Social Security Number		
		YYDDPP-NNNNN	CBP Assigned Number		
		XXXXXXXXXXXXXXXXXX	Passport Number		
		XAAA	SCAC		
In these codes, <i>N</i> = number, <i>X</i> = alphanumeric, <i>YY</i> = the last two digits of the calendar year when the number is assigned, <i>DDPP</i> = the district/port code where the number is assigned.					
For goods intended to be entered into an FTZ (Foreign Trade Zone), for the purposes of the Importer Security Filing, the ISF Importer is deemed to be the Applicant for FTZ Admission and is the same “importer number” as would be reported in Form 3461.					
Not Used	NM110	706	Entity Relationship Code	X	ID 2/2
Not Used	NM111	98	Entity Identifier	O	ID 2/2
Not Used	NM112	1035	Name Last or Organization Name	O	AN 1/60
	NM113	26	Country Code	O	ID 2/3
			Code identifying country		
			Code identifying the ISO country of issuance of the Passport in NM109. This field is required when NM108 = ‘PN’		

Segment:	DMG Demographic Information
Position:	050
Loop:	NM1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To supply demographic information
Syntax Notes:	1 If either DMG01 or DMG02 is present, then the other is required.
Semantic Notes:	1 DMG02 is the date of birth. 2 DMG07 is the country of citizenship. 3 DMG09 is the age in years.
Comments:	
Notes:	This segment may be required when the NM1 Identification Code at NM108 = 'PN' (Passport Number) or NM108 = '34' (Social Security Number).

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
DMG01	1250	Date Time Period Format Qualifier	X ID 2/3
		Code indicating the date format, time format, or date and time format	
		DB Date Expressed in Format MMDDCCYY	
DMG02	1251	Date Time Period	X AN 1/35
		Expression of a date, a time, or range of dates, times or dates and times	
		Date of Birth expressed as MMDDCCYY.	
Not Used	DMG03	1068 Gender Code	O ID 1/1
Not Used	DMG04	1067 Marital Status Code	O ID 1/1
Not Used	DMG05	C056 Composite Race or Ethnicity Information	10 X
Not Used	DMF06	1066 Citizenship Status Code	O ID 1/2
Not Used	DMG07	26 Country Code	O ID 2/3
Not Used	DMG08	659 Basis of Information	O ID 1/2
Not Used	DMG09	380 Quantity	O R 1/15
Not Used	DMG10	1270 Code List Qualifier Code	O ID 1/3
Not Used	DMG11	1271 Industry Code	O AN 1/3
Not Used	DMG12	26 Country Code	O ID 2/3

Segment:	REF	Reference Identification
Position:	050	
Loop:	NM1	Optional
Level:		
Usage:	Optional	
Max Use:	10	
Purpose:	To specify identifying information	
Syntax Notes:	1 At least one of REF02 or REF03 is required.	
	2 If either C04003 or C04004 is present, then the other is required.	
	3 If either C04005 or C04006 is present, then the other is required.	
Semantic Notes:	1 REF04 contains data relating to the value cited in REF02.	
Comments:		
Notes:	This segment is used to identify the Bond Holder. Bond information is mandatory for all Add or Replace transactions when the Shipment Type code = 01, 02, 07, 08, or 10 and the ISF Submission Type is not 5 or 6.	

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier	M ID 2/3
			Code qualifying the Reference Identification	
			Values accepted by USCBP to identify the bond holder.	
			ANI	Customs and Border Protection [CBP] assigned Importer Identifier
			EI	Employer's Identification Number
			SY	Social Security Number
	REF02	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			Required.	
			A reference number identifying the Bond Holder based on qualifier in REF01.	
			Valid formats for the Bond Holder are:	
			NN-NNNNNNXX	Internal Revenue Service (IRS) Number
			YYDDPP-NNNN	CBP Assigned Number
			NNN-NN-NNNN	Social Security Number
Not Used	REF03	352	Description	X AN 1/80
	REF04	C040	Reference Identifier	O
			To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	
M	C04001	128	Reference Identification Qualifier	M ID 2/3
			Code qualifying the Reference Identification	
			Value accepted by USCBP.	
			BIN	U.S. Customs and Border Protection (USCBP) Bond Identifier
			Bond Type	
M	C04002	127	Reference Identification	M AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			Bond Type - left justified for 1 digit.	
			If the Bond Activity Code is '16' and the Bond Type is '9', the Surety Code (SCI) and Bond Reference Number (SBN) must be provided in the N9 above.	
			ISF values accepted by USCBP.	
			8	Continuous
			9	Single Transaction
			A Bond Type 9 may only be used with a Bond Activity Code 16.	

C04003	128	Reference Identification Qualifier	X	ID 2/3
		Code qualifying the Reference Identification		
		Required. Value accepted by USCBP.		
		BIC		U.S. Customs and Border Protection (USCBP) Bond Activity Reference
				Bond Activity Code
C04004	127	Reference Identification	X	AN 1/30
		Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier		
		Required. Bond Activity Code - left justified for 2 digits.		
		If the Bond Activity Code is '16' and the Bond Type is '9', the Surety Code (SCI) and Bond Reference Number (SBN) must be provided in the N9 above.		
		Values accepted by USCBP.		
		01		Importer or Broker
		02		Custodian of Bonded Merchandise
		03		International Carrier
		04		Foreign Trade Zone Operator
		16		ISF Bond

Segment: **P4** U.S. Port Information
Position: 050
Loop: P4 Mandatory
Level:
Usage: Mandatory
Max Use: 1
Purpose: To transmit identifying information for a port
Syntax Notes:
Semantic Notes:

- 1 P401 is used for customs district and port code (census schedule D).
- 2 P402 is the estimated date of arrival.
- 3 P403 is used for number of bills of lading.
- 4 P404 is the Facilities Information and Resources Management System (FIRMS) Code.
- 5 P405 is the estimated time of arrival for P402.

Comments:

Data Element Summary				
	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	P401	310	Location Identifier Code which identifies a specific location Port of Entry Code if available; otherwise enter '0000' in P401. Port of Arrival of the conveyance into Mexico. Refer to CAMIR Appendix O for valid codes. 0000 Port Not Disclosed	M AN 1/30
M	P402	373	Date Date expressed as CCYYMMDD Estimated Date of Arrival if available; otherwise enter current date in P402. Date as CCYYMMDD	M DT 8/8
Not Used	P403	380	Quantity	O R 1/15
Not Used	P404	310	Location Identifier	O AN 1/30
Not Used	P405	337	Time	O TM 4/8
Not Used	P406	373	Date	O DT 8/8
Not Used	P407	337	Time	O TM 4/8

Segment: **LX** Assigned Number
Position: 060
Loop: LX Mandatory
Level:
Usage: Mandatory
Max Use: 1
Purpose: To reference a line number in a transaction set
Syntax Notes:
Semantic Notes:
Comments:
Notes:

Refer to Notes associated with LX-01 element.
 1. Start with one (1) and increment by one (1) for each iteration of the Loop.
 2. Only one P4/LX loop is allowed per transaction.

Data Element Summary

M	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
	LX01	554	Assigned Number	M N0 1/6
			Number assigned for differentiation within a transaction set	
			One LX segment per bill in the 309 transaction set. Increment this element by +1 for each BOL reported in subsequent segments.	

Segment:	N9	Reference Identification
Position:	090	
Loop:	LX	Mandatory
Level:		
Usage:	Optional	
Max Use:	999	
Purpose:	To transmit identifying information as specified by the Reference Identification Qualifier	
Syntax Notes:	1	At least one of N902 or N903 is required.
	2	If N906 is present, then N905 is required.
	3	If either C04003 or C04004 is present, then the other is required.
	4	If either C04005 or C04006 is present, then the other is required.
Semantic Notes:	1	N906 reflects the time zone which the time reflects.
	2	N907 contains data relating to the value cited in N902.
Comments:		

Data Element Summary			
Ref.	Data	Name	Attributes
Des.	Element		
M	N901	128	Reference Identification Qualifier
			M ID 2/3
		Code qualifying the Reference Identification	
		Values accepted by USCBP. At least one BM or OB must be reported per ISF filing. Both 6B and MB are optional fields.	
		6B	U.S. Customs Service (USCS) Entry Number
		BM	Bill of Lading Number
			House Bill – is defined as a bill of lading issued under a Master Bill. For ISF, this is the House Bill reported to CBP in AMS. If multiple House Bills exist, the N9 record is repeated accordingly
		MB	Master Bill of Lading
			Master Bill – is defined as a bill of lading covering at least one or more underlying house bills of lading. For ISF, this is the Master Bill reported to CBP in AMS. If multiple Master Bills exist, the N9 record is repeated accordingly. Reporting of a master bill is optional.
		OB	Ocean Bill of Lading
			Regular Bill – is defined as a non-Master bill of lading with NO UNDERLYING house bills. For ISF, this is the bill reported to CBP in AMS, which is also referred to as “Straight Bill” or “Simple Bill”. If multiple Regular Bills exist, the N9 record is repeated accordingly.
		HO	For SAT: The HO qualifier in N901 is used by Carriers to report the master bill of Lading associated with the house bill
			In Mexican transactions
		MXC	The MXC qualifier is used by carriers To report the Mexican CAAT number
		MXE	The MXE qualifier is used by carriers To report the export bonded ware-
			House number. This is required for Mexican export transactions and Usage. Refer to schedule located in http://www.gob.mx/refx12appendix

MXI

The MXI qualifier is used by carriers to Report the Mexican import bonded Warehouse number. This is required For Mexican import transactions and Usage. Refer to schedule located in <http://gob.mx/refx12appendix> CAMIR Appendix O contains valid Mexican warehouse numbers

M	N902	127	Reference Identification	O AN 1/30
Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
A code representing the Bill of Lading number or entry number associated with a shipment.				
For any bill of lading, the format is the CAAT of the bill of lading issuer concatenated with the bill of lading number				
The entry number (6B) must be normalized and formatted as follows: FFFNNNNNNNN.				

Not Used	N903	369	Free-form Description	X AN 1/45
Not Used	N904	373	Date	O DT 8/8
Not Used	N905	337	Time	X TM 4/8
Not Used	N906	623	Time Code	O ID 2/2
Not Used	N907	C040	Reference Identifier	X

Not Used	C04001	128	Reference Identification Qualifier	M ID 2/3
Not Used	C04002	127	Reference Identification	M AN 1/30
Not Used	C04003	128	Reference Identification Qualifier	M ID 2/3
Not Used	C04004	128	Reference Identification	M AN 1/30
Not Used	C04005	128	Reference Identification Qualifier	M ID 2/3
Not Used	C04006	128	Reference Identification	M AN 1/30

Segment:	N1 Name
Position:	100
Loop:	N1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.
Notes:	The ISF-10 Security Filing requires (BY, CS, CN, LG, SE and ST) N1 Loops are present. The ISF-5 Security Filing requires (BKP and ST) N1 Loops are present. This is a mandatory record that identifies the type of commercial entity whose identity is being reported. When reporting a commercial entity, the N1, N3 and N4 segments must be used if the Entity Identifier Code in the N101 field is equal to code SE (Seller), BY (Buyer), ST (Ship To Party), CS (Consolidator), LG (Stuffing Location) or BKP (Booking Party). The N1 segment identifies the entity being reported. The N3 and N4 segments provide parsed fields for address and geographical location reporting to accommodate the various conventions found in the formats of non US addresses. Alternatively, a DUNS number may be used instead of reporting name and address for any of these parties. Additionally, a FIRMS code may be used to report ST (Ship To). When a DUNS number or FIRMS code is used, only the SF30 record is required.

Data Element Summary			
Ref.	Data	Name	Attributes
Des.	Element		
M	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		Values accepted by USCBP for ISF purposes to identify the entity being reported.	
		BKP Booking Party	
		BY Buying Party (Purchaser)	
		CN Consignee	
		See special consideration for consignee at N103 when Shipment Type = '03'	
		CS Consolidator	
		LG Location of Goods	
		Scheduled Container Stuffing Location	
		SE Selling Party	
		ST Ship To Party	
		TIN Mexican Consignee/Importer Taxpayer number	
N102	93	Name	O AN 1/60
		Free-form name	
		Use a "Last, First M Initial" format. USCBP will accept up to 35 alpha/numeric characters in this element.	

N103	66	<p>For SAT: Required by SAT when N101 is 'TIN'. SAT will accept 35 alphanumeric Character in this element</p> <p>Identification Code Qualifier X ID 1/2</p> <p>Code designating the system/method of code structure used for Identification Code (67)</p> <p>This qualifier describes the type of Identification Code being reported in the N104 field. This field is mandatory if an Identification Code is being supplied in lieu of name and address. This field is mandatory if the entity identifier is CN.</p> <p>1 D-U-N-S Number, Dun & Bradstreet</p> <p>9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix</p> <p>24 Employer's Identification Number</p> <p>34 Social Security Number</p> <p>When used, Full Name may be required in the N102 and Date of Birth may be required in the following DMG segment.</p> <p>CW U.S. Customs and Border Protection [USCBP] assigned consignee number</p> <p>FR Facilities Information Requirements Management System [FIRMS] code.</p> <p>PN Passport Number</p> <p>When used, the Full Name is required in the N102 and Date of Birth is required in the following DMG segment.</p> <p>TIN Mexican Consignee's/importer's Taxpayer's Identification number</p> <p>ZB U.S. Customs and Border Protection [USCBP] encrypted consignee identification</p>
N104	67	<p>Identification Code X AN 2/80</p> <p>Code identifying a party or other code</p> <p>A code describing the entity reported in the N101 field. The N103 field must be present when a code is supplied in this field. This field is mandatory when N101 = CN</p> <p>Valid values for Entity Identifier Qualifier are:</p> <p>1 = DUNS Number Valid format is: NNNNNNNNN This qualifier may only be used when N101 = SE, BY, ST, LG, CS, or BKP</p> <p>9 = DUNS+4 Number Valid format is: NNNNNNNNNNNNN This qualifier may only be used when N101 = SE, BY, ST, LG, CS, or BKP</p> <p>24 = Employer Identification Number (IRS #) Valid format is: NN-NNNNNNNXX This qualifier may only be used when N101 = SE, BY, or CN</p> <p>34 = Social Security Number Valid format is: NNN-NN-NNNN This qualifier may only be used when N101 = SE, BY, or CN</p> <p>CW = CBP-assigned Number Valid format is: YYDDPP-NNNN This qualifier may only be used when N101 = SE, BY, or CN</p>

FR = Facility Information Resource Management System (FIRMS) Code
Valid format is: **ANNN**
This qualifier may only be used when N101 = **ST**

ZB = CBP encrypted Consignee ID
Valid format is: **-CCCCCCCCCCCC**
This qualifier may only be used when N101 = **SE, BY, or CN**

PN = Passport Number
Valid format is: **XXXXXXXXXXXXXXXXXX**
This qualifier may only be used when N101 = **CN** for Shipment Types 03, 05, 06, or 11. Use 2 field concatenation formula as follows:

Format the PN as: 2-digit Country Code (Country of passport issuance) followed by Passport Number. See CAMIR Appendix G for Country Codes. Enter XX if country Code is not known.

In these codes, N = number, X = alphanumeric, YY = the last two digits of the calendar year when the number is assigned, DDPP = the district/port code where the number is assigned and C = character.

For SAT:
If N101 is 'TIN' this is required. Formula is TIN000000XXX. SAT Will accept 50 alphanumeric characters in this element .

Not Used	N105	706	Entity Relationship Code	O	ID 2/2
Not Used	N106	98	Entity Identifier Code	O	ID 2/3

Segment: **N3** Address Information
Position: 110
Loop: N1 Optional
Level:
Usage: Optional
Max Use: 2
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:
Notes: This is a conditional record used to transmit lines of the entity's address data. .

Data Element Summary

M	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
	N301	166	Address Information	M AN 1/55
			Address information	
			SAT will accept up to 35 alpha/numeric characters for this element.	
	N302	166	Address Information	O AN 1/55
			Address information	
			Additional address data. SAT will accept up to 35 alpha/numeric characters for this element.	

Segment:	N4 Geographic Location
Position:	120
Loop:	N1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To specify the geographic place of the named party
Syntax Notes:	1 If N406 is present, then N405 is required.
Semantic Notes:	
Comments:	<p>1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.</p> <p>2 N402 is required only if city name (N401) is in the U.S. or Canada.</p>
Notes:	This is a conditional record that provides data pertaining to the city, country, and postal code associated with the address of the entity reported in the N1 segment. .

Data Element Summary				
Ref.	Data			
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>	
N401	19	City Name	O	AN 2/30
		Free-form text for city name		
		Required for all countries		
M	N402	156	State or Province Code	O ID 2/2
		Code (Standard State/Province) as defined by appropriate government agency		
		Required. Reference http://www.unece.org/cefact/locode/service/sublocat.htm for State or Province Codes.		
	N403	116	Postal Code	O ID 3/15
		Code defining international postal zone code excluding punctuation and blanks (zip code for United States)		
		Postal codes for all countries.		
M	N404	26	Country Code	O ID 2/3
		Code identifying the country		
		Required. Code Source 5 - Codes for representation of Name of Countries found in ISO 3166 (latest release). Refer to CAMIR Appendix G. 2 alpha character field.		
Not Used	N105	309	Location Qualifier	X ID 1/2
Not Used	N406	310	Location Identifier	O AN 1/30
	N407	1715	Country Subdivision Code	O ID 1/3
		Code identifying the country subdivision.		
		Required if applicable.		
Not Used	N408	1702	Postal Code formatted	O AN 3/20

Segment: **DMG** Demographic Information
Position: 125
Loop: N1 Optional
Level:
Usage: Optional
Max Use: 1
Purpose: To supply demographic information
Syntax Notes: 1 If either DMG01 or DMG02 is present, then the other is required.
Semantic Notes: 1 DMG02 is the date of birth.
2 DMG07 is the country of citizenship.
3 DMG09 is the age in years.

Comments:

Data Element Summary

	Ref.	Data	Name	Attributes
	Des.	Element		
	DMG01	1250	Date Time Period Format Qualifier	X ID 2/3
			Code indicating the date format, time format, or date and time format	
			DB Date Expressed in Format MMDDCCYY	
	DMG02	1251	Date Time Period	X AN 1/35
			Expression of a date, a time, or range of dates, times or dates and times	
			Date of Birth expressed as MMDDCCYY.	
Not Used	DMG03	1068	Gender Code	O ID 1/1
Not Used	DMG04	1067	Marital Status Code	O ID 1/1
Not Used	DMG05	C056	Composite Race or Ethnicity Information	10 X
Not Used	DMG06	1066	Citizenship Status Code	O ID ½
Not Used	DMG07	26	Country Code	O ID 2/3
Not Used	DMG08	659	Basis of Information	O ID ½
Not Used	DMG09	380	Quantity	O R 1/15
Not Used	DMG10	1270	Code List Qualifier Code	X ID 1/3
Not Used	DMG11	1271	Industry Code	X AN 1/15
Not Used	DMG12	26	Country Code	O ID 2/3

Segment:	M12	In-bond Identifying Information
Position:	150	
Loop:	M12	Optional
Level:		
Usage:	Optional	
Max Use:	1	
Purpose:	To transmit in-bond and FROB information	
Syntax Notes:	1	Only one of M1202 or M1206 may be present.
	2	If M1206 is present, then M1208 is required.
	3	If either M1208 or M1209 is present, then the other is required.
	4	If either M1210 or M1211 is present, then the other is required.
Semantic Notes:	1	M1203 is a four-digit numeric census schedule D when identifying a U.S. port, and a three-digit numeric memorandum D when identifying a Canadian port. It is the port of destination if M1201 is "61". It is the port of export if M1201 is "62" or "63".
	2	M1204 is five-digit numeric census schedule K. It is the foreign port of destination if M1201 is "62" or "63".
	3	M1207 identifies the carrier to whom liability is transferred.
Comments:	1	If M1202 does not contain the paperless entry number, then M1206 is required.
	2	M1205 is the value in whole dollars of the in-bond movement. Use twenty dollars per kilo if value is unknown.
Notes:	If an ISF-10 is filed, the M12 is not required.	
	If an ISF-5 is filed, the M12 (with underlying R4) is required.	

Data Element Summary				
	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	M1201	581	Customs Entry Type Code	M ID 2/3
Code defining the type of entry assigned by U.S. Customs				
Values accepted by USCBP.				
		00	Freight Remains On Board [FROB]	
		62	Transportation Exportation	
		63	Immediate Exportation	
Not Used	M1202	601	Customs Entry Number	X AN 1/15
Not Used	M1203	310	Location Identifier	O AN 1/30
Not Used	M1204	310	Location Identifier	O AN 1/30
Not Used	M1205	602	Customs Shipment Value	O AN 2/8
Not Used	M1206	603	Inbond Control Number	X AN 1/50
Not Used	M1207	140	Standard Carrier Alpha Code	O ID 2/4
Not Used	M1208	128	Reference Identification Qualifier	X ID 2/3
Not Used	M1209	127	Reference Identification	X AN 1/30
Not Used	M1210	91	Transportation Method Type Code	X ID 1/2
Not Used	M1211	182	Vessel Name	X AN 2/28
Not Used	M1212	1273	Yes/No Condition or Response	O ID 1/1

Segment:	R4 Port or Terminal
Position:	160
Loop:	M12 Optional
Level:	
Usage:	Optional
Max Use:	2
Purpose:	Contractual or operational port or point relevant to the movement of the cargo
Syntax Notes:	1 If either R402 or R403 is present, then the other is required.
Semantic Notes:	
Comments:	1 R4 is required for each port to be identified.
Notes:	The ISF-5 requires two occurrences of the R4 segment to communicate Place of Delivery and Foreign Port of Unlading/ (Port of Discharge).

Data Element Summary				
Ref.	Data	Name	Attributes	
Des.	Element			
M	R401	115 Port or Terminal Function Code	M	ID 1/1
		Code defining function performed at the port or terminal with respect to a shipment		
		Values accepted by USCBP.		
		D Port of Discharge (Operational)		
		Port at which cargo is unloaded from vessel		
		Foreign Port of Unlading.		
		E Place of Delivery (Contractual)		
		Place at which cargo leaves its care and custody of carrier		
R402	309	Location Qualifier	X	ID 1/2
		Code identifying type of location		
		Values accepted by USCBP.		
		K Census Schedule K		
		Valid codes for Schedule K (US Army Corps of Engineers Schedule K Code) can be found in appendix F of the CAMIR document.		
		UN United Nations Location Code (UNLOCODE)		
		UNLoc codes (United Nations Location Code) can be found at http://www.unece.org/cefact/locode/		
	R403	310 Location Identifier	X	AN 1/30
		Code which identifies a specific location		
Not Used	R404	114 Port Name	O	AN 2/24
Not Used	R405	26 Country Code	O	ID 2/3
Not Used	R406	174 Terminal Name	O	AN 230
Not Used	R407	113 Pier Number	O	AN 1/4
Not Used	R408	156 State/Province Code	O	ID 2/2

Segment:	VID	Conveyance Identification
Position:	170	
Loop:	VID	Optional
Level:		
Usage:	Optional	
Max Use:	1	
Purpose:	To identify a conveyance and its attributes	
Syntax Notes:		
Semantic Notes:	1 VID12 is the Census Schedule K code for the foreign port of loading on a vessel. 2 VID13 is the Standard Carrier Alpha Code (SCAC) of the Haulage Rights Carrier.	
Comments:		
Notes:	The combination of the VID02 and VID03 fields comprise the container number. A specific Container may be reported only once within the same Bill of Lading. For ISF purposes, the VID segment is required to preserve the looping structure in order to report the manufacturer, if required, and/or harmonized tariff number and country of origin code.	

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	VID01	40	Equipment Description Code Code identifying type of equipment used for shipment Refer to CAMIR Appendix I for valid Equipment Description Codes. For ISF purposes, if no container is being reported, code 'NC' must be used to preserve the looping structure. If VID01 = 'NC' - Non-containerized, then enter 'NA' in VID02 and VID03.	M ID 2/2
	VID02	206	Equipment Initial Prefix or alphabetic part of an equipment unit's identifying number Required in USCBP ocean manifest if equipment initial precedes the equipment number. If VID01 = 'NC' - Non-containerized, enter 'NA' in this field.	O AN 1/4
M	VID03	207	Equipment Number Sequencing or serial part of an equipment unit's identifying number (pure numeric form for equipment number is preferred) Required in ocean manifest if cargo is containerized. If VID01 = 'NC' - Non-containerized, enter 'NA' in this field.	M AN 1/15
Not Used	VID04	225	Seal Number	O AN 2/15
Not Used	VID05	225	Seal Number	O AN 2/15
Not Used	VID06	567	Equipment Length	O NO 4/5
Not Used	VID07	65	Height	O R 1/8
Not Used	VID08	189	Width	O R 1/8
	VID09	225	Equipment Type Code Code identifying equipment type Minimum of 4 alpha/numeric characters. Refer to CAMIR Appendix M for valid codes.	O ID 4/4
Not Used	VID10	322	Load/Empty Status Code	O ID 1/1
Not Used	VID11	56	Type of Service Code	O ID 2/2
Not Used	VID12	310	Location Identifier	O AN 1/30
Not Used	VID13	140	Standard Carrier Alpha Code	O ID 2/4
Not Used	VID14	127	Reference Identification	O AN 1/80
Not Used	VID15	156	State or Province Code	X ID 2/2
Not Used	VID16	26	Country Code	X AN 2/3
Not Used	VID17	127	Reference Identification	O AN 1/80
Not Used	VID18	1715	Country Subdivision Code	X ID 1/3
Not Used	VID19	512	Import/Export code	O ID 1/1

VID20	761	Equipment Number Check Digit	O N0 1/1
		Number which designates the check digit applied to a piece of equipment	

Segment:	N1 Name
Position:	184
Loop:	N1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.
Notes:	Required. This N1 segment is reserved for communicating the manufacturer. Note: When Filing an ISF-5 this field is not required however must be populated to preserve the looping structure. Use 'ZZ' in N101 to start the loop The N1 segment identifies the manufacturer. The N3 and N4 segments provide parsed fields for address and geographical location reporting to accommodate the various conventions found in the formats of non US addresses. When submitting a name in the N102 field, both the N3 and N4 segments must be present. If data is presented in the N103 and N104 fields, then the N3 and N4 segments are not used.

Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		MF Manufacturer of Goods	
			When filing an ISF-10, manufacturer data must be submitted to CBP.
		ZZ Mutually Defined	
			When filing an ISF-5, use "ZZ" at N101 to preserve the looping structure.
N102	93	Name	X AN 1/60
		Free-form name	
		Enter manufacturer name. Enter 'Unknown' when M101 = 'ZZ'.	
		When submitting a manufacturer name in this field, both the N3 and N4 segments must be present. Do not populate this field if an Identification Code is used in the N104 field.	
N103	66	Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		Values accepted by USCBP. This qualifier describes the type of Identification Code being reported in the N104 field. This field is mandatory if an Identification Code is being supplied in lieu of name and address.	
		1 D-U-N-S Number, Dun & Bradstreet	
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	

	N104	67	Identification Code	X	AN 2/80
			Code identifying a party or other code		
			Required for any ID in N103.		
			A code describing the entity reported in the N101 field. The N103 field must be present when a code is supplied in this field.		
			Valid values for Entity Identifier Qualifier are:		
			1 = DUNS Number		
			Valid format is: NNNNNNNNN		
			9 = DUNS+4 Number		
			Valid format is: NNNNNNNNNNNNN		
Not Used	N105	706	Entity Relationship Code	O	ID 2/2
Not Used	N106	98	Entity Identifier Code	O	ID 2/3

Segment: **N3** Address Information
Position: 190
Loop: N1 Optional
Level:
Usage: Optional
Max Use: 1
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:
Notes:

This is a conditional segment used to transmit lines of the manufacturer's address data. Only either the N102 or N104 can be provided for each N1 segment. If the N1 segment contains an entity name, then the N3 and N4 segments MUST be used. If the N1 segment contains an Identification Code in place of a name, or if N101 = 'ZZ', then the N3 and N4 segments are not used.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N301	166	Address Information Address information SAT will accept up to 35 alpha/numeric characters for this element.	M AN 1/55
	N302	166	Address Information Address information Additional address data. SAT will accept up to 35 alpha/numeric characters for this element.	O AN 1/55

Segment:	N4 Geographic Location
Position:	190
Loop:	N1 Optional
Level:	
Usage:	Optional
Max Use:	1
Purpose:	To specify the geographic place of the named party
Syntax Notes:	1 If N406 is present, then N405 is required.
Semantic Notes:	
Comments:	<p>1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.</p> <p>2 N402 is required only if city name (N401) is in the U.S. or Canada.</p>
Notes:	This is a conditional record that provides data pertaining to the city, country, and postal code associated with the address of the manufacturer reported in the N1 segment. Only either the N102 or N104 can be provided for each N1 segment. If the N1 segment contains an entity name, then the N3 and N4 segments MUST be used. If the N1 segment contains an Identification Code in place of a name, or if N101 = 'ZZ', then the N3 and N4 segments are not used.

Data Element Summary				
Ref.	Data			
Des.	Element	Name	Attributes	
N401	19	City Name	O	AN 2/30
		Free-form text for city name		
		ISF transaction accept only 19 alpha/numeric characters.		
M	N402	156 State or Province Code	O	ID 2/2
		Code (Standard State/Province) as defined by appropriate government agency		
		Reference http://www.unece.org/cefact/locode/service/sublocat.htm for State or Province Codes.		
	N403	116 Postal Code	O	ID 3/15
		Code defining international postal zone code excluding punctuation and blanks (zip code for United States)		
		Postal codes for all countries.		
M	N404	26 Country Code	O	ID 2/3
		Code identifying the country		
		Required. Code Source 5 - Codes for representation of Name of Countries ISO 3166 (latest release). Refer to CAMIR Appendix G for valid codes. 2 alpha character field.		
Not Used	N405	309 Location Qualifier	X	ID 1/2
Not Used	N406	310 Location Identifier	O	AN 1/30
	N407	1715 Country Subdivision Code	X	ID 1/3
		Code Identifying the country Subdivision		
		Required if Applicable		

Segment: **N10 Quantity and Description**

Position: 190

Loop: N10 Optional (Must Use)

Level:

Usage: Optional (Must Use)

Max Use: 1

Purpose: To indicate line item quantity, description, marks and numbers, commodity code, weight, and customs value

Syntax Notes: 1 If either N1004 or N1005 is present, then the other is required.

2 If either N1006 or N1013 is present, then the other is required.

3 If either N1007 or N1008 is present, then the other is required.

Semantic Notes: 1 N1009 is the U.S. Customs bar code number for line release.

2 N1011 is the country of the manufacturer of the goods.

3 N1012 is the country of the final destination of the goods.

4 N1013 is the currency of the value of N1006.

Comments:

Notes: Do not use the character selected to serve as Subelement Separator (ISA16) in description. Do not exceed 999 lines of description.
At least one N10 segment is required for an ISF.

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
Not Used	N1001	380 Quantity	O R 1/15
Not Used	N1002	369 Free-Form Description	O R 1/15
Not Used	N1003	87 Marks and Numbers	O R 1/15
	N1004	23 Commodity Code Qualifier	O R 1/15
		Code identifying the commodity coding system used for Commodity Code	
	N1005	22 Commodity Code	X AN 1/30
		Code describing the commodity or group of commodities	
		Required if M1201 is '62' (TE) OR '63' (IE)	
Not Used	N1006	602 Customs Shipment Value	X AN 2/8
Not Used	N1007	188 Weight Unit Code	X ID 1/1
Not Used	N1008	81 Weight	X R 1/10
Not Used	N1009	127 Reference Identification	O AN 1/80
Not Used	N1010	599 Manifest Unit Code	O ID 1/3
	N1011	26 Country Code	O ID 2/3
		Code identifying the country	
		ISO 2 alpha country code. This code represents the country of origin	
		Of the shipment. Refer to CAMIR Appendix G for valid codes.	

Segment: **SE** Transaction Set Trailer
Position: 200
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)
Syntax Notes:
Semantic Notes:
Comments: 1 SE is the last segment of each transaction set.

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **GE** **Functional Group Trailer**
Position: 220
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of a functional group and to provide control information
Syntax Notes:
Semantic Notes: 1 The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.
Comments: 1 The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	GE01	97	Number of Transaction Sets Included Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M N0 1/6
M	GE02	28	Group Control Number Assigned number originated and maintained by the sender	M N0 1/9

Segment: **IEA** Interchange Control Trailer
Position: 240
Loop:
Level:
Usage: Mandatory
Max Use: 1
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	IEA01	I16	Number of Included Functional Groups A count of the number of functional groups included in an interchange	M N0 1/5
M	IEA02	I12	Interchange Control Number A control number assigned by the interchange sender	M N0 9/9